

## NCTS-IN06A1


#### **Product Features**

Mainly used in the wiring system between work area correspondence leading-out terminal and distribution wiring frames connection. As well as used in the housing synthesis wiring system between user correspondence leading out terminal and patch panel.

#### **Meets Cabling Standards:**

CAT6A Cable is designed for improve crosstalk performance between cablesapplying in 1000Base-T Enternet with up to 500MHZ bandwidth.HDPE insulation and pair shield design make the cable with excellent shielding & anti-EMI peformance.









# CAT 6A U/FTP 4P+F Twisted Pair Indoor Cable | 23AWG | Copper

### **Technical Specifications**

**MODEL: NCTS-IN06A1** 

Brand:	NCTS	Color:	light GREY
Conductor Material:	Copper	Conductor Size:	23AWG (0.58mm)
Conductor:	Solid	Twisted Pair:	4PAIRS
Structure:	4P+F Twisted Pair	Jacket Material	PVC
Insulation Material:	PE	Insulation Diameter:	1.0mm(±0.02mm)
Insulation Thickness:	0.18mm	Jacket Thickness:	0.65mm(±0.02mm)
Outer diameter:	6.5mm(±0.2mm)	Stretching Resistance:	(max)450N
Impedance:	100±15%Ω	Frequency	500MHz
Flame Retardancy Standard:	CM / CMR	Reference standard:	YD/T2001-1019, ISO/IEC 11801, ANSI / TIA / EIA568-B, UL444







