

NCTS-INF062

CAT 6 FTP 4P Twisted Pair Indoor
Cable | 23AWG | CCA


NCTS-INF062

Product Features

Mainly Used in the wiring system between area correspondence leading-out terminal and distribution wiring frames connection. As well as used in housing synthesis wiring system between user correspondence leading out terminal and patch panel.

Meets Cabling Standards:

10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T The effective bandwidth of data layer is 1Gbit/s, the Maximum transmission distance is 100 meter. Cross isolation structure effectively avoid the crosstalk between each pair of the cable. Double shield structure, make the cable have stronger anti-interference ability to the outside world and transmit the signal in strictest confidence.



CAT 6 FTP 4P Twisted Pair Indoor Cable | 23AWG | CCA

Technical Specifications

Model: NCTS-INF062

Input		Characteristics	
Conductor	CCA	Rated Temperature :	-40°C~+70°C
	4P*0.5mm 23AWG	Impedance:	100 ±15Ω at 1-250MHz
Insulation	Material : HDPE	Insulation Resistance :	10000MΩ.km
	Insulation Dia: 0.98±0.02mm	Capacitance :	< 330PF/100m
	blue-white/blue , green-white/green orange-white/orange, brown-white/brown	NVP:	68%
Filler	PE Cross	Stretching Resistance:	(max)250N
Shielded	AL Foil + Paper	Installation Temperature:	-30°C~+50°C
	Braid : N/M	Minimum Bending Radius:	4D
Outter Jacket	Material : PVC		
	Thickness:0.6mm		
	External O.D : 6.3±0.2mm		
	Flammability Text : CMR		
Packing	Color:blue /white/grey or customized		
	305 meters /pull out box (1000ft)		

