

NETWORK CABLE Outdoor

NCTS-ONSF061 SFTP 4P Twisted Pair Cable SFTP Category-6

Application

Mainly Used in the wiring system between area correspondence leading-out terminal and distribution wiring frames connection. As well as used in housing synthesis wiring system between user correspondence leading out terminal and patch panel.

Cabling Standards Meet:

10BASE-T、100BASE-TX、100BASE-T4、1000BASE-T  
The effective bandwidth of data layer is 1Gbit/s, the Maximum transmission distance is 100 meter.  
Cross isolation structure effectively avoid the crosstalk between each pair of the cable. Double shield structure, make the cable have stronger anti-interference ability to the outside world and transmit the signal in strictest confidence.

Specification	
Conductor	CCA
	4P*23AWG/0.58mm
Insulation	High Density Polyethylene (HDPE )
	O.D:0.98±0.02mm
	blue-white/blue , green -white/green orange-white/orange , brown-white/brown
Filler	PE Cross
Inner Jacket	PVC
Outer Jacket	LDPE
	Thickness:0.6mm
	External O.D : 6.3±0.2mm
	Flammability Text : CMR
	Color: black color
Packing	305 meters /roll, wooden reel with small stic



Characteristics	
Rated Temperature :	-40℃~+70℃
Impedance:	100 ±15Ω
Inner shielded :	AL-foil 125%(min) coverage
Outer shielded:	Braiding 60% (min) coverage
Capacitance :	< 330PF/100m
Frequency:	250MHZ
Stretching Resistance:	(max)400N
Installation Temperature:	-30℃~50℃
Minimum Bending Radius:	4D
Flame Retardancy Standard:	CM、CMR