

VGA CABLE  
MALE TO MALE

# NCTS-VGA 3+4 AM AM VGA 3+4 MALE TO MALE CABLE

## NCTS-VGA 3+4 AM AM

### Product Features

VGA cable is with a three-row -15pin DE15- connector,It used to connect and send signals between computers and monitors,Television, Laptop,Projector and so on .It Can support various VGA resolutions,ranging from 320x400px @70 Hz / 320x480px @60 Hz (12.6 MHz of signal bandwidth) to 1280x1024px (SXGA) @85 Hz (160 MHz) and up to 2048x1536px (QXGA) @85 Hz (388 MHz).



# NCTS-VGA 3+4 AM AM

## VGA 3+4 MALE TO MALE CABLE

### Technical Specifications

#### MODEL: NCTS-VGA 3+4 AM AM

##### SPECIFICATIONS:

Version	3+2/3+4/3+5/3+6/3+9
Connector Type:	15 PIN VGA Male To VGA Male
Plug Mould	Injection
Conductor	Bare Copper/CCS
Connector Plug	Nickel Plated/Gold plated
Conductor Guage	30AWG/28AWG/26AWG/24AWG/22AWG..
Insulation	Foamed PE
Shield	Aluminum Foil & Braid
Jacket	PVC
Jacket Dia	5.5-8.0mm
Mesh	With/Without Nylon/Cotton Mesh
Ferrite	2 ferrite
Connector	Gold Plated 1μ/2μ/3μ/5μ
Resulation	320x400px @70 Hz / 320x480px @60 Hz (12.6 MHz of signal bandwidth) to 1280x1024px (SXGA) @85 Hz (160 MHz) and up to 2048x1536px (QXGA) @85 Hz (388 MHz)
Length	1.5m to 80m

##### ELECTRICAL SPECIFICATIONS:

Conductor Resistance	@°20C Max. 30AWG: 376.96Ω/Km 28AWG : 237.25Ω/Km
Normal Capacitance	58PF/M
Normal impedance with Tolerance	75±5Ω
Maximum Resolution Supported	2048x1536
Insulation Resistance	10MΩ-KM min at °20C DC 500V
Dielectric Strength	AC 500V/1 Minute
PHYSICAL CHARATERISTICS:	
Voltage Rating	30V
Minimum Bend Radius	85mm
Contact Resistance	2 ohm max
Working Temperature	-25 °C-80°C

