

QSALE-B200U THERMAL BARCODE PRINTER

GTIN: 6295151551622

Product Features

- Support both receipt printing and lable printing



- Support missing paper alarm function



- Support IAP online upgrade
- Multiple interface, USB / USB+LAN
USB+WIFI



QSALE-B200U

THERMAL BARCODE PRINTER

GTIN: 6295151551622

Model		QSALE-B200U	
Print mode	Label print mode		Receipt print mode
Printing method	Direct Thermal		
Resolution	203 DPI		
Max.print speed	127 mm/s Max.	180 mm/s	
Max.print width	76 mm		
RAM	4M		
Flash	4M		
Interfaces	USB		
Print head temperature detection	Thermistor		
Print head position detection	Micro Switch		
Media			
Media type	Thermal roll paper, thermal adhesive paper		
Media width	20~80mm		
Media roll diameter	Max.83 mm		
Media inner diameter	25mm~38mm		
Paper exit method	Tearing off		
Media thickness	0.06 ~ 0.19 mm		
Fonts/Graphics/Symbologies			
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14		
2D bar code	PDF417、QRCODE、DataMatrix		
Character sizes	Commonly used in single-byte fonts; FONT 1 to FONT 8, K, TST24.BF2,TSS24.BF2		
Emulation	TSPL	ESC / POS	
Physical Features			
Dimension	183*140*132.5mm		
Weight	0.9 kg		
Operation	5~45 °C, Humidity:RH 10 ~ 80%		
Storage environment	-40 ~ 55 °C, Humidity:93% RH		
Power Input	DC 24V/2.5A		
Print head life	50 KM		
Operating system	WINDOWS/ Android / IOS		