

GTIN: 6295151551691

Product Features

• Support both receipt printing and lable printing





• Support missing paper alarm function







- Support IAP online upgrade
- Multiple interface, USB / USB+LAN **USB+WIFI**





















Ductr.



QSALE-B200WTHERMAL BARCODE PRINTER

GTIN: 6295151551691

GTIN. 02931313310	701	
Model	QSALE-B200W	
Print mode	Label print mode	Receipt print mode
Printing method	Direct Thermal	
Resolution	203 DPI	
Max.print speed	127 mm/s Max.	180 mm/s
Max.print width	76 mm	
RAM	4M	
Flash	4M	
Interfaces	USB WIFI	
Print head temperature	Thermistor	
detection		
Print head position	Micro Switch	
detection		
Media		
Media type	Thermal roll paper, thermal adhesive paper	
Media width	20~80mm	
Media roll diameter	Max.83 mm	
Media inner diameter	25mm~38mm	
Paper exit method	Tearing off	
Media thickness	0.06 ~ 0.19 mm	
Fonts/Graphics/Symbologies		
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 /	
EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTN		N8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A/
	UPCA+2 /UPCA+5/ UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY /ITF14 / EAN14	
2D bar code	PDF417、QRCODE、DataMatrix	
Character sizes	Commonly used in single-byte fonts; FONT 1 to FONT 8, K, TST24.BF2,TSS24.BF2	
Emulation	TSPL	ESC/POS
Physical Features		
Dimension	183*140*132.5mm	
Weight	0.9 kg	
Operation	5~45 °C, Humidity:RH 10 ~ 80%	
Storage environment	-40 ~ 55 °C, Humidity:93% RH	
Power Input	DC 24V/2.5A	
Print head life	50 KM	
Operating system	WINDOWS/ Android / IOS	

Website: www.ncts.co | www.ncts.cn

E-mail: info@ncts.co | info@ncts.cn

