

QSALE-B200U THERMAL BARCODE PRINTER

GTIN: 6295151551622

Product Features

- Support both receipt printing and lable printing



- Support missing paper alarm function



- Support IAP online upgrade
- Interface, USB



QSALE-B200U

THERMAL BARCODE PRINTER

GTIN: 6295151551622

Model		QSALE-B200U
Print mode	Label print mode	Receipt print mode
Printing method	Direct Thermal	
Resolution	203 DPI	
Max.print speed	180 mm/s	
Max.print width	76 mm	
RAM	4M	
Flash	4M	
Interfaces	USB	
Print head temperature detection	Thermistor	
Print head position detection	Micro Switch	
Media		
Media type	Thermal roll paper, thermal adhesive paper	
Media width	20~80mm	
Media roll diameter	Max.83 mm	
Media inner diameter	25mm~38mm	
Paper exit method	Tearing off	
Media thickness	0.06 ~ 0.19 mm	
Fonts/Graphics/Symbologies		
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14	
2D bar code	PDF417、QRCODE、DataMatrix	
Character sizes	Commonly used in single-byte fonts; FONT 1 to FONT 8, K, TST24.BF2, TSS24.BF2	
Emulation	TSPL	ESC / POS
Physical Features		
Dimension	183*140*132.5mm	
Weight	0.9 kg	
Operation	5~45 °C, Humidity:RH 10 ~ 80%	
Storage environment	-40 ~ 55 °C, Humidity:93% RH	
Power Input	DC 24V/2.5A	
Print head life	50 KM	
Operating system	WINDOWS/ Android / IOS	