

QSALE-R100W THERMAL RECEIPT PRINTER

GTIN: 6295151551677

Product Features

- 58/80/83mm paper width available
- Make printer maintained easily
- Reliable cutter from cutter jammed prevent cutter from cutter jammed
- Compatible with ESC/POS commands
- IAP function supports firmware update within 5S



QSALE-R100W

THERMAL RECEIPT PRINTER

GTIN: 6295151551677

Model	QSALE-R100W
Resolution	203 DPI
Printing method	Direct thermal
Paper width	79.5±0.5mm
Print width	72mm
Column capacity	576 dots/line
Printing speed	260 mm/s
Interface	USB WIFI
Line spacing	3.75mm (Adjustable by commands)
Paper type	Continuous paper
Paper thickness	0.06mm-0.08mm
Paper width	80mm
Paper roll outer diameter	80mm±0.5mm
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) PC863(Canadian) / PC865(Nordic) / West Europe / Greek / East Europe/ WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	96 Kbytes(USB, USB+Serial), 256 Kbytes(Lan, USB+Lan)
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 100~240V, 50 ~ 60Hz
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	0.9 Kg
Dimensions	134 × 130 × 132mm(D*W*H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)
Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printhead life	150 km
Software	
Emulation	ESC/POS
Driver	Windows / Linux / Mac OS / Android