

NCTS-QSALE-R120W THERMAL RECEIPT PRINTER

GTIN: 6295151552148

Product Features

- Multiple interface connections, auto-cutter, wall mountable.
- Support both 58/80mm width paper. (USB+WIFI)
- Support page mode (USB+WIFI)
- Support QR Code.
- Support Windows, Linux, Andorid, IOS, OPOS, and MacOS



android



iOS



Windows



Linux



NCTS-QSALE-R120W

THERMAL RECEIPT PRINTER

GTIN: 6295151552148

Model		QSALE-R120W
Printing method:	Direct thermal	
Printing speed:	260 mm/s	
Paper width:	80 mm / 58 mm	
Printing Width:	72 mm	
Column capacity:	576 dots/line or 512 dots/line	
Interface:	USB+WIFI	
Line spacing:	3.75mm (Adjustable by commands)	
Character size:	ANK, Font A: 1.5×3.0mm (12×24 dots), Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm (24×24 dots)	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) PC860(Portuguese)/ PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866 (Cyrillic#2) PC852(Latin2) / PC858 / Iran11 / Latvian / Arabic / PTI51(1251)	
1D barcode:	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128	
2D barcode:	QR CODE	
Input buffer:	USB: 64 Kbytes / USB+Lan: 128 Kbytes 128 Kbytes	
NV Flash:	256 Kbytes	
Power		
Power adapter input:	AC 110–240V, 50–60Hz	
Printer input:	DC 24V / 2.5A	
Cash drawer:	DC 24V / 2.5A	
Physical Characteristics		
Weight:	0.96 Kg	
Dimensions:	170×130×125 mm	
Environmental Requirements		
Work environment:	Temperature (0–45°C), humidity (10–80%)	
Storage environment:	Temperature (-10–60°C), humidity (10–90%)	
Reliability		
Auto cutter:	Partial	
Cutter life:	1.5 million cuts	
Print head life:	150 Km	
Software		
Emulation:	ESC / POS	
Driver:	Windows / JPOS / Linux / OPOS / Android / Mac	
Utility:	Windows & Linux test Utility	
SDK:	iOS, Android, Windows	